



Authorized Distributor



WX Monitor Datasheet



WX | Monitor

DYNICS WX Monitor is a drop-in replacement for legacy WebLink and Panellink systems.

Key Features

- 100~240VAC / 24VDC
- Drop in Replacement for Legacy Systems
- No Moving parts

Display Specifications

Size	Resolution	View Angle	Contrast	Brightness	Aspect Ratio
15"	XGA 1024 x 768	H: -80°/+80°, V: -80°/+80°	600:1	350 nits	4:3
17"	SXGA 1280 x 1024	H: -85°/+85°, V: -80°/+80°	1000:1	350 nits	5:4
Lens	5-Wire Analog Resistive (Touch Screen) / Protective Polycarbonate Lens (Non-Touch)				
LCD Life	50,000 Hour Backlight Half-Life				
Enclosure	NEMA 4 Powder Coat Finish / NEMA 4X Stainless Steel				
Power Entry	100~240VAC / 24VDC				
Temperature	Operating: 0° - 50°C (32° - 122°F) Non-Operating: -25° - 60°C (-13° - 140°F)				
Compliance	European Union Directive 2011/65/EU (RoHS)				
Warranty	24-Month limited warranty. Extended warranty available, contact DYNICS for details.				

Dimensions, Weight and Power Consumption

	15"	17"
Height (Bezel)	12.160" (308.8mm)	14.100" (358.3mm)
Width (Bezel)	15.390" (390.0mm)	17.150" (435.7mm)
Depth	3.250" (82.5mm)	3.220" (81.9mm)
Weight	14 lbs.*	18 lbs.*
Power Consumption	25 Watts**	30 Watts**

*Weights are approximate, contact DYNICS for details.

**Power Consumption based on maximum ratings, actual ratings vary significantly based on components used.

Mechanical Drawings

17"	15"	100~240VAC Power Entry	24VDC Power Entry

All measurements are in inches and pounds, unless noted. Pictures and drawings are not to scale. Estimated weight may change depending on options. DYNICS reserves the right to change, modify, upgrade, or discontinue any part of this datasheet without any prior notice.

