



# ODTC<sup>®</sup> Power & Control Unit (PCU)

## ***Specifications***

**Dimensions (WxDxH Horizontally Placed):** 256.5 mm x 414.5 mm x 58 mm <sup>\*1)</sup>

**Interface:** SiLA, Ethernet (RJ45 connector)

**Weight:** Approx. 5.5 kg

**AC Input:** 100-240 V / 50/60 Hz (1250 W)

**DC Output:** 24 Vdc / 1200W

**Protection Class:** I (according DIN EN 61140)

**Fuses:** 2 x T12A / 250 V

## ***Environmental Conditions***

**Tolerable Relative Humidity:**

*Operation:* 30-80% <sup>\*4)</sup>

*Transportation and storage:* 30-80% <sup>\*4)</sup>

**Temperature:**

*Operation:* +15 °C to +32 °C [+59 °F to +90 °F]

*Transportation and storage:* -10 °C to +60 °C [+14 °F to +140 °F]

1) Note: The ODTC<sup>®</sup> Power & Control Unit can be positioned vertically or horizontally.

2) Condensate can prevent the ODTC<sup>®</sup> from operating properly and can damage the ODTC<sup>®</sup>.

**[Click Here to Request a Quote](#)**

***For an official quote, please contact us at [info@tekmatic.com](mailto:info@tekmatic.com)***